

In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser

■ N10U083U02B - Anodized Grey


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	3007
Lamp category	LED	Mountings	Suspension
Power (W)	38.5W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Indirect, Direct		Beam Angle DIR: 73°		
LED type	Top LED				
Light distribution	Symmetric		h(m)	E(lx)	D(m)
Optical type	Diffused light				
Beam angle (°)	73		1	1275	1.47
Beam angle C90-270 (°)	81		2	319	2.95



Luminous flux lumineuse
3007 lm

Electrical

Frequency (Hz)	50/60	Insulation class
Dimmable	No	
Driver	Integrated	
Driver type	Non Dimmable	
Emergency	Without	

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	5
Length (mm)	845

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Up & Down 3000K Micro-Prismatic Diffuser



5

Metal cover. Suspension Up & Down.
100 mm (Colour Anodized Grey)
08.9058.02



500 mm micro-prismatic diffuser.
Highly efficient multilayer diffuser
that, thanks to its unique
microprismatic texture, provides a
glare free UGR<19 light beam
08.0114.00



5

Metal cover. Suspension Up & Down.
100 mm
08.9058.06



5

Metal cover. Suspension Up & Down.
100 mm (Colour White)
08.9058.40



Suspension kit
08.0030



5

Metal cover. Suspension Up & Down.
100 mm (Colour Black)
08.9058.NS



Power supply rose
08.0031.00