



In-Finity 100 Suspension Up & Down 4000K General Lighting Dali

N10U084G02BDA - Anodized Grey


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	3358
Lamp category	LED	Mountings	Suspension
Power (W)	38.5W/m	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Lighting type Indirect, Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 103 Beam angle C90-270 (°) 107



3358 lm

Beam A	ngle DIK	: 103
h(m)	E(l ×)	D(m)
1	921	2.54
2	230	5.07
3	102	7.61
4	58	10.14
5	37	12.68

Electrical

Frequency (Hz) 50/60 Insulation class Dimmable Yes Driver Integrated Dimmable DALI Driver type

Emergency Without

Physical

Color Anodized Grey Orientation Fixed Weight (kg) Length (mm) 845

Note

 $Opal\,Diffuser:\,Diffuse,\,glare\,free\,and\,uniform\,lighting\,throughout\,the\,room.\,/\,Emergency:\,Emergency\,Module\,And Control of Control$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 100 Suspension Up & Down 4000K General Lighting Dali







500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0111.00

Metal cover. Suspension Up & Down. 100 mm 08.9058.06

Metal cover. Suspension Up & Down. 100 mm (Colour Anodized Grey) 08.9058.02







Metal cover. Suspension Up & Down. 100 mm (Colour White) 08.9058.40

Suspension kit 08.0030

Power supply rose. Dali 08.0031.00.DA



Metal cover. Suspension Up & Down. 100 mm (Colour Black) 08.9058.NS