



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali

■ N10U30B4U30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Mountings	Suspension
Lamp category	LED	Environment	Indoor dry location
Power (W)	38.5W/m		
CCT (K)	4000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light

Electrical


Frequency (Hz)	50/60	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		
Emergency	Without		

Physical

Color	White
Orientation	Fixed
Weight (kg)	21.40
Length (mm)	3095

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser Dali



5

Metal cover. Suspension Up & Down.
100 mm
08.9058.06



5

Metal cover. Suspension Up & Down.
100 mm (Colour White)
08.9058.40



5

Metal cover. Suspension Up & Down.
100 mm (Colour Anodized Grey)
08.9058.02



500 mm micro-prismatic diffuser.
Highly efficient multilayer diffuser
that, thanks to its unique
microprismatic texture, provides a
glare free UGR<19 light beam
08.0114.00



5

Metal cover. Suspension Up & Down.
100 mm (Colour Black)
08.9058.NS



Suspension kit
08.0030



Power supply rose. Dali
08.0031.00.DA