



# In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser

## ■ N10U194U14B - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

## Main specifications

Number of heads	1	Net lumen (lm)	7600
Lamp category	LED	Mountings	Suspension
Power (W)	38.5W/m	Environment	Indoor dry location
CCT (K)	4000K		
CDI	00		

#### Optical

Lighting type Indirect, Direct
LED type Top LED
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 73
Beam angle C90-270 (°) 81



h(m)	E( <b>l</b> x)	D(m
1	3224	1.47
2	806	2.95
3	358	4.42
4	201	5.90
5	129	7.37

Beam Angle DIR: 73°

#### Electrical

Frequency (Hz)	50/60	Insulation class	- 1
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

#### Physical

Color	Black
Orientation	Fixed
Weight (kg)	17.70
Length (mm)	1970

#### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 100 Suspension Up & Down 4000K Micro-Prismatic Diffuser







Metal cover. Suspension Up & Down. 100 mm (Colour Anodized Grey) 08.9058.02



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0114.00



Metal cover. Suspension Up & Down. 100 mm (Colour White) 08.9058.40



Suspension kit 08.0030



Metal cover. Suspension Up & Down. 100 mm (Colour Black) 08.9058.NS



Power supply rose 08.0031.00