

In-Finity 100 Suspension Up & Down Emergency 4000K General Lighting Dali

■ **N10UEM4G02BDA - Anodized Grey**

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Lamp category	LED	Environment	Indoor dry location
Power (W)	38.5W/m		
CCT (K)	4000K		
CRI	80		
Mountings	Suspension		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light

Electrical


Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI
	1
Emergency	Without
Insulation class	I

Physical

Color	Anodized Grey
Orientation	Fixed
Length (mm)	1400

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Up & Down Emergency 4000K General Lighting Dali



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0111.00



Metal cover. Suspension Up & Down.
100 mm
08.9058.06



Metal cover. Suspension Up & Down.
100 mm (Colour Anodized Grey)
08.9058.02



Metal cover. Suspension Up & Down.
100 mm (Colour White)
08.9058.40



Power supply rose. Dali
08.0031.00.DA



Metal cover. Suspension Up & Down.
100 mm (Colour Black)
08.9058.NS



Suspension kit
08.0030