



In-Finity 100 Suspension Up & Down Emergency 4000K General Lighting

■ N10UEM4G02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

| | | | |
|----------------------|------------|--------------------|---------------------|
| Lamp category | LED | Environment | Indoor dry location |
| Power (W) | 38.5W/m | | |
| CCT (K) | 4000K | | |
| CRI | 80 | | |
| Mountings | Suspension | | |

Optical

| | |
|---------------------------|------------------|
| Lighting type | Indirect, Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Diffused light |

Electrical

| | |
|-------------------------|--------------|
| Dimmable | No |
| Driver | Integrated |
| Driver type | Non Dimmable |
| Emergency | Without |
| Insulation class | I |

Physical

| | |
|--------------------|---------------|
| Color | Anodized Grey |
| Orientation | Fixed |
| Length (mm) | 1400 |

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Up & Down Emergency 4000K General Lighting



Suspension kit
08.0030



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0111.00



Metal cover. Suspension Up & Down. 100 mm (Colour White)
08.9058.40



Power supply rose
08.0031.00



Metal cover. Suspension Up & Down. 100 mm (Colour Anodized Grey)
08.9058.02



Metal cover. Suspension Up & Down. 100 mm
08.9058.06



Metal cover. Suspension Up & Down. 100 mm (Colour Black)
08.9058.NS