





## ■ N10UFC4U14BDA - Black


LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

## Main specifications

Number of heads	1	Net lumen (lm)	4327
Lamp category	LED	Mountings	Suspension
Power (W)	38.5W/m	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

## Optical

Lighting type Indirect, Direct
LED type Top LED
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 73
Beam angle C90-270 (°) 81



h(m)	E( <b>l</b> x)	D(m
1	1835	1.47
2	459	2.95
3	204	4.42
4	115	5.90
5	73	7.37

Beam Angle DIR: 73°

Electrical	

Frequency (Hz)	50/60	Insulation class
Dimmable	Yes	
Driver	Integrated	

**Driver type**Dimmable DALI
1


**Emergency** Without


## **Physical**

Color	Black
Orientation	Fixed
Weight (kg)	8.20

#### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.






# In-Finity 100 Suspension Up & Down Flat Corner 4000K Micro-Prismatic Diffuser Dali



Metal cover. Suspension Up & Down. 100 mm (Colour White) 08.9058.40



Suspension kit 08.0030



Metal cover. Suspension Up & Down. 100 mm 08.9058.06



Power supply rose. Dali 08.0031.00.DA



Metal cover. Suspension Up & Down. 100 mm (Colour Black) 08.9058.NS



Metal cover. Suspension Up & Down. 100 mm (Colour Anodized Grey) 08.9058.02



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam

