



In-Finity 35 Recessed Trim 3000K General Lighting

■ N35T193G14B - Black

 ${\tt LED\ modular\ system\ for\ recessed\ Trim\ installation, including\ LED\ luminaires, aluminum\ installation\ profile\ and\ profile\ p$ diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications


Number of heads 1	
Lamp category LED	,
Power (W) 41V	/
CCT (K) 300	0K
CRI 80	

Net lumen (lm) Mountings Environment

Recessed trim Indoor dry location

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



Luminous flux luminaire 2301 lm

Beam Angle:		107
h(m)	E(lx)	D(m
1	846	2.63
2	211	5.26
3	94	7.90
4	53	10.53
5	34	13 16

Electrical

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable

Physical

Color	Black
Orientation	Fixed
Trim	yes
Recessed depth (mm)	120
Weight (kg)	4.48

Emergency Insulation class

Length (mm)

1970

Without

Note

 $Opal\ Diffuser: Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Recessed Trim 3000K General Lighting







500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00

Metal cover. Recessed Trim. 35 mm (Colour Black) 08.9051.NS

Metal cover. Recessed Trim. 35 mm (Colour Anodized Grey) 08.9051.02



Metal cover. Recessed Trim. 35 mm (Colour White) 08.9051.40