

In-Finity 35 Recessed Trim 3000K Micro-Prismatic Diffuser Dali

N35T053U14BDA - Black

 ${\tt LED\ modular\ system\ for\ recessed\ Trim\ installation, including\ LED\ luminaires, aluminum\ installation\ profile\ and\ profile\ p$ diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications


Number of heads	1
Lamp category	LED
Power (W)	13W
CCT (K)	3000K
CRI	80

Net lumen (lm) Mountings Environment

Recessed trim Indoor dry location

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	76
Beam angle C90-270 (°)	64



Luminous flux luminaire 511 lm

Beam Angle:		75°
h(m)	E(l x)	D(m
1	331	1.25
2	83	2.50
3	37	3.76
4	21	5.01
5	13	6.26

Electrical

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI

Insulation class

Emergency

Without

Physical

Color	Black	Length (mm)	565
Orientation	Fixed		
Trim	yes		
Recessed depth (mm)	120		
Weight (kg)	1.28		

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Recessed Trim 3000K Micro-Prismatic Diffuser Dali



Metal cover. Recessed Trim. 35 mm (Colour White) 08.9051.40 500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00 Metal cover. Recessed Trim. 35 mm (Colour Black) 08.9051.NS



Metal cover. Recessed Trim. 35 mm (Colour Anodized Grey) 08.9051.02