





LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications


D
W
00K

Net lumen (lm) Mountings Environment

Recessed trim Indoor dry location

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



h(m) $E(I_X)$ D(m) 654 2.63 2 164 5.26 3 73 7.90 4 41 10.53 5 26 13.16

Beam Angle: 107°

1779 lm

Electrical

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI

Without **Emergency**

Insulation class





Physical

Color	Black	Length (mm)	1405
Orientation	Fixed		
Trim	yes		
Recessed depth (mm)	120		
Weight (kg)	3.19		

Note

 $Opal\ Diffuser: Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Recessed Trim 4000K General Lighting Dali







500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00 Metal cover. Recessed Trim. 35 mm (Colour Anodized Grey) 08.9051.02 Metal cover. Recessed Trim. 35 mm (Colour Black) 08.9051.NS



Metal cover. Recessed Trim. 35 mm (Colour White) 08.9051.40