





# In-Finity 35 Recessed Trim 4000K General Lighting

# ■ N35T054G14B - Black

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

### Main specifications


Number of heads	1
Lamp category	LED
Power (W)	13W
CCT (K)	4000K
CRI	80

Net lumen (lm) Mountings Environment

712 Recessed trim Indoor dry location

# Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



Without

h(m)  $E(I_X)$ D(m) 262 2.63 2 5.26 65 3 29 7.90 4 16 10.53 5 10 13.16

Beam Angle: 107°

Luminous flux luminaire 712 lm

**Emergency** Insulation class

-	lectrical	
_	iecu icai	

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable

#### Physical

Color Orientation	Black Fixed	Length (mm)	565
Trim	yes		
Recessed depth (mm)	120		
Weight (kg)	1.28		



#### Note

 $Opal\ Diffuser: Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 35 Recessed Trim 4000K General Lighting







Metal cover. Recessed Trim. 35 mm (Colour Black) 08.9051.NS



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00



Metal cover. Recessed Trim. 35 mm (Colour White) 08.9051.40