
Recessed trim

Indoor dry location









## In-Finity 35 Recessed Trim Dihedral Corner 3000K Micro-Prismatic Diffuser Dali

#### N35TDC3U30BDA - White


LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

### Main specifications

Number of heads	1	Net lumen (In
Lamp category	LED	Mountings
Power (W)	22.5W	Environment
CCT (K)	3000K	
CRI	80	

#### Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	76
Beam angle C90-270 (°)	64



Luminous flux	luminaire
1022 lm	

Emergency Insulation class Without

Beam Angle:		75°
h(m)	E( <b>l</b> x)	D(m)
1	662	1.25
2	166	2.50
3	74	3.76
4	41	5.01
5	26	6.26

#### **Electrical**

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI
	1

### Physical


Color	White	Length (mm)	546
Orientation	Fixed		
Trim	yes		
Recessed depth (mm)	120		
Weight (kg)	3.16		

#### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 35 Recessed Trim Dihedral Corner 3000K Micro-Prismatic Diffuser Dali







Metal cover. Recessed Trim. 35 mm (Colour Anodized Grey) 08.9051.02



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00



Metal cover. Recessed Trim. 35 mm (Colour White) 08.9051.40