

FLOS









In-Finity 35 Recessed Trim Dihedral Corner 4000K General Lighting Dali

N35TDC4G02BDA - Anodized Grey

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications	
N 1 61 1	4

Number of heads Lamp category Power (W) CCT (K) CRI	1 LED 22.5W 4000K 80	Net lumen (lm) Mountings Environment	1424 Recessed trim Indoor dry location
Optical Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)	Direct Top LED Symmetric Diffused light 110 110	90° 60° 30° 523 cd Luminous flux lu	Beam Angle: 107° h(m) E(lx) D(m) 1 523 2.63 2 131 5.26 3 58 7.90 4 33 10.53 5 21 13.16 minaire
Electrical Frequency (Hz) Voltage (V) Dimmable Driver Driver type	50/60 220.00 Yes Integrated Dimmable DALI 1	1424 lm Emergency Insulation class	Without I
Physical Color Orientation Trim Recessed depth (mm) Weight (kg)	Anodized Grey Fixed yes 120 3.16	Length (mm)	546
Note			

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Recessed Trim Dihedral Corner 4000K General Lighting Dali



Metal cover. Recessed Trim. 35 mm (Colour Anodized Grey) 08.9051.02 Metal cover. Recessed Trim. 35 mm (Colour Black) 08.9051.NS 500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00



Metal cover. Recessed Trim. 35 mm (Colour White) 08.9051.40