


FLOS









In-Finity 35 Recessed Trim Dihedral Corner 4000K General Lighting Dali

N35TDC4G30BDA - White

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

| Main specifications Number of heads Lamp category Power (W) CCT (K) CRI | 1 LED 22.5W 4000К 80 | Net lumen (lm) Mountings Environment | 1424 Recessed t Indoor dry | |
|--|--|---|----------------------------------|--|
| Optical Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°) | Direct Top LED Symmetric Diffused light 110 110 | 90° 60° 30° 523 cd Luminous flux lu 1424 lm | 90° 60° 30° uminaire | Beam Angle: 107° h(m) E(lx) D(m) 1 523 2.63 2 131 5.26 3 58 7.90 4 33 10.53 5 21 13.16 |
| Electrical Frequency (Hz) Voltage (V) Dimmable Driver Driver type | 50/60 220.00 Yes Integrated Dimmable DALI 1 | Emergency Insulation class | Without I | |
| Physical Color Orientation Trim Recessed depth (mm) Weight (kg) | White Fixed yes 120 3.16 | Length (mm) | 546 | |

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Recessed Trim Dihedral Corner 4000K General Lighting Dali



Metal cover. Recessed Trim. 35 mm (Colour White) 08.9051.40 500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00 Metal cover. Recessed Trim. 35 mm (Colour Anodized Grey) 08.9051.02



Metal cover. Recessed Trim. 35 mm (Colour Black) 08.9051.NS