


## In-Finity 35 Recessed Trim Emergency 3000K General Lighting

### ■ N35TEM3G02B - Anodized Grey

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.



### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 1643                |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Recessed trim       |
| <b>Power (W)</b>       | 28W   | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 3000K |                       |                     |
| <b>CRI</b>             | 80    |                       |                     |

### Optical

|                           |                |                               |     |
|---------------------------|----------------|-------------------------------|-----|
| <b>Lighting type</b>      | Direct         | <b>Beam angle C90-270 (°)</b> | 110 |
| <b>LED type</b>           | Top LED        |                               |     |
| <b>Light distribution</b> | Symmetric      |                               |     |
| <b>Optical type</b>       | Diffused light |                               |     |
| <b>Beam angle (°)</b>     | 110            |                               |     |

### Electrical

|                    |              |                         |   |
|--------------------|--------------|-------------------------|---|
| <b>Voltage (V)</b> | 220.00       | <b>Insulation class</b> | I |
| <b>Dimmable</b>    | No           |                         |   |
| <b>Driver</b>      | Integrated   |                         |   |
| <b>Driver type</b> | Non Dimmable |                         |   |
| <b>Emergency</b>   | With         |                         |   |

### Physical

|                            |               |
|----------------------------|---------------|
| <b>Color</b>               | Anodized Grey |
| <b>Orientation</b>         | Fixed         |
| <b>Recessed depth (mm)</b> | 120           |
| <b>Weight (kg)</b>         | 3.19          |
| <b>Length (mm)</b>         | 1405          |

### Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



## In-Finity 35 Recessed Trim Emergency 3000K General Lighting



---

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room  
08.0109.00



5

---

Metal cover. Recessed Trim. 35 mm  
(Colour Anodized Grey)  
08.9051.02



5

---

Metal cover. Recessed Trim. 35 mm  
(Colour Black)  
08.9051.NS



5

---

Metal cover. Recessed Trim. 35 mm  
(Colour White)  
08.9051.40