





N35TFC3G30B - White

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications


Number of heads	1
Lamp category	LED
Power (W)	22.5W
CCT (K)	3000K
CRI	80

Net lumen (lm) Mountings Environment

Recessed trim Indoor dry location



Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



2 121 5.26 3 54 7.90 4 30 10.53 5 19 13.16

h(m)

Beam Angle: 107°

 $E(I_X)$

483

D(m)

2.63

Electrical

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Driver	Integrated
Driver type	Non Dimmable

Without **Emergency** Insulation class

568

1315 lm

Length (mm)

Color	White
Orientation	Fixed
Trim	yes
Recessed depth (mm)	120
Weight (kg)	3.16

Physical

Orientation	Fixed
Trim	yes
Recessed depth (mm)	120
Weight (kg)	3.16



Note

 $Opal\ Diffuser: Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Recessed Trim Flat Corner 3000K General Lighting



Metal cover. Recessed Trim. 35 mm (Colour White) 08.9051.40 500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00 Metal cover. Recessed Trim. 35 mm (Colour Black) 08.9051.NS



Metal cover. Recessed Trim. 35 mm (Colour Anodized Grey) 08.9051.02