



# In-Finity 35 Surface 3000K General Lighting Dali

## N35S143G30BDA - White

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

## Main specifications


Number of heads	1
Lamp category	LED
Power (W)	28W
CCT (K)	3000K
CRI	80

1643 Net lumen (lm) Mountings Surface **Environment** 

Indoor dry location

## Optical

Lighting type	Direct
LED type ⊤	op LED
<b>Light distribution</b> S	ymmetric
Optical type	Diffused light
Beam angle (°)	10
Beam angle C90-270 (°) 1	10



2 151 5.26 3 67 7.90 4 38 10.53 5 24 13.16

h(m)

Beam Angle: 107°

 $E(I_X)$ 

604

D(m)

2.63

Electrical	
Electrical	

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI

Without **Emergency** Insulation class

1643 lm

### **Physical**

Color	White
Orientation	Fixed
Weight (kg)	3.19
Length (mm)	1405

#### Note

 $Opal\ Diffuser: Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

## In-Finity 35 Surface 3000K General Lighting Dali







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40