



## In-Finity 35 Surface 3000K Micro-Prismatic Diffuser

■ **N35S053U14B - Black**

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.



85  
3135  
38




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	511
<b>Lamp category</b>	LED	<b>Mountings</b>	Surface
<b>Power (W)</b>	13W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	80		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	76
<b>Beam angle C90-270 (°)</b>	64



<b>Beam Angle:</b>	75°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	331	1.25	
2	83	2.50	
3	37	3.76	
4	21	5.01	
5	13	6.26	

Luminous flux luminaire  
511 lm

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		

### Physical

<b>Color</b>	Black
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	1.28
<b>Length (mm)</b>	565

### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 35 Surface 3000K Micro-Prismatic Diffuser



5



5

500 mm micro-prismatic diffuser.  
Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam  
08.0112.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey)  
08.9050.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White)  
08.9050.40



5



5

Metal cover. Surface / Suspension Down. 35 mm  
08.9050.06

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black)  
08.9050.NS