



# In-Finity 35 Surface 3000K Micro-Prismatic Diffuser

#### N35S253U02B - Anodized Grey

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

## Main specifications


Number of heads	1
Lamp category	LED
Power (W)	50W
CCT (K)	3000K
CRI	80

Net lumen (lm) Mountings Surface

Environment Indoor dry location

#### Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	76
Beam angle C90-270 (°)	64



Without

2300 lm

2 373 2.50 3 166 3.76 93 5.01 4 5 60 6.26

Beam Angle: h(m)

E(lx)

1490

75°

D(m)

1.25

Flectrical	
Liccuicai	

Frequency (Hz)	50/60	Emergency
Voltage (V)	220.00	Insulation class
Dimmable	No	
Driver	Integrated	
Driver type	Non Dimmable	

### Physical

Color	Anodized Grey	
Orientation	Fixed	
Weight (kg)	5.75	
Length (mm)	2530	

### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 35 Surface 3000K Micro-Prismatic Diffuser








Metal cover. Surface / Suspension Down. 35 mm 08.9050.06

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40

500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS