




L []]<u>8</u> 35 38



In-Finity 35 Surface 4000K General Lighting

N35S254G30B - White

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications Number of heads Lamp category Power (W) CCT (K) CRI	1 LED 50W 4000K 80	Net lumen (lm) Mountings Environment	3203 Surface Indoor dry loc	cation
Optical Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)	Direct Top LED Symmetric Diffused light 110 110	90° 60° 30° 1178 cd Luminous flux lu 3203 lm	90° 60° 30°	Beam Angle: 107° h(m) E(lx) D(m) 1 1178 2.63 2 294 5.26 3 131 7.90 4 74 10.53 5 47 13.16
Electrical Frequency (Hz) Voltage (V) Dimmable Driver Driver Driver type Physical Color Orientation Weight (kg) Length (mm)	50/60 220.00 No Integrated Non Dimmable White Fixed 5.75 2530	Emergency Insulation class	Without I	

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Surface 4000K General Lighting



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00





Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS