







N35S144U30BDA - White

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications


Number of heads	1
Lamp category	LED
Power (W)	28W
CCT (K)	4000K
CRI	80

Net lumen (lm) Mountings Surface Environment

Indoor dry location

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	76
Beam angle C90-270 (°)	64



h(m) E(lx)D(m) 1.25 896 2 2.50 224 3 100 3.76 5.01 4 56 5 36 6.26

Beam Angle:

75°

Luminous flux luminaire 1384 lm

Electrical

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI

Without **Emergency** Insulation class









8

35 38







White
Fixed
3.19
1405

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 $mm.\ In\ normal\ use,\ it\ uses\ the\ same\ power\ consumption\ as\ the\ standard\ In-Flnity.\ In\ emergency\ use,\ it\ emits\ 10\%$ of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Surface 4000K Micro-Prismatic Diffuser Dali







Metal cover. Surface / Suspension Down. 35 mm 08.9050.06 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40 500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS