

## FLOS









## In-Finity 35 Surface Dihedral Corner 3000K General Lighting Dali

## N35SDC3G02BDA - Anodized Grey

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications Number of heads Lamp category Power (W) CCT (K) CRI	1 LED 22.5W 3000K 80	Net lumen (lm) Mountings Environment	1315 Surface Indoor dry	location
Optical Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)	Direct Top LED Symmetric Diffused light 110 110	90° 60° 30° 483 cd Luminous flux 1315 lm		Beam Angle: 107°   h(m) E(lx) D(m)   1 483 2.63   2 121 5.26   3 54 7.90   4 30 10.53   5 19 13.16
Electrical Frequency (Hz) Voltage (V) Dimmable Driver Driver type	50/60 220.00 Yes Integrated Dimmable DALI 1	Emergency Insulation class	Without I	
Physical Color Orientation Weight (kg) Length (mm)	Anodized Grey Fixed 3.16 546			

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

## In-Finity 35 Surface Dihedral Corner 3000K General Lighting Dali



Down. 35 mm 08.9050.06

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00





Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS