



In-Finity 35 Surface Dihedral Corner 3000K Micro-Prismatic Diffuser

N35SDC3U02B - Anodized Grey

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.


Main specifications

Number of heads	1	Net lumen (lm)	1022
Lamp category	LED	Mountings	Surface
Power (W)	22.5W	Environment	Indoor
CCT (K)	3000K		
CRI	80		




Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	76
Beam angle C90-270 (°)	64



Beam Angle:	75°		
h(m)	E(lx)	D(m)	
1	662	1.25	
2	166	2.50	
3	74	3.76	
4	41	5.01	
5	26	6.26	

Luminous flux luminaire
1022 lm



Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	3.16
Length (mm)	546

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 35 Surface Dihedral Corner 3000K Micro-Prismatic Diffuser



5



5

500 mm micro-prismatic diffuser.
Highly efficient multilayer diffuser
that, thanks to its unique
microprismatic texture, provides a
glare free UGR<19 light beam
08.0112.00

Metal cover. Surface / Suspension
Down. 35 mm (Colour White)
08.9050.40

Metal cover. Surface / Suspension
Down. 35 mm (Colour Anodized Grey)
08.9050.02



5



5

Metal cover. Surface / Suspension
Down. 35 mm (Colour Black)
08.9050.NS

Metal cover. Surface / Suspension
Down. 35 mm
08.9050.06