75°

D(m)

1.25

2.50

3.76 5.01 6.26

Beam Angle:

E(lx)

717

179

80

h(m)


2


3











## In-Finity 35 Surface Dihedral Corner 4000K Micro-Prismatic Diffuser Dali

## N35SDC4U02BDA - Anodized Grey


Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

## Main specifications

Number of heads	1	Net lumen (lm)	1107
Lamp category	LED	Mountings	Surface
Power (W)	22.5W	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

### Optical

Direct
Top LED
Symmetric
Diffused light
76
64



1107 lm

	4	45
717 cd 30°	5	29
ninous flux luminaire		

Without

#### Electrical

Frequency (Hz)	50/60	Emergency
Voltage (V)	220.00	Insulation class
Dimmable	Yes	
Driver	Integrated	
Driver type	Dimmable DALI	

## Physical

Color	Anodized Gre
Orientation	Fixed
Weight (kg)	3.16
Length (mm)	546

### Note

 $Micro-Prismatic \ Diffuser: Highly \ efficient \ multilayer \ diffuser \ that, thanks \ to \ its \ unique \ micro-prismatic \ texture,$ provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 35 Surface Dihedral Corner 4000K Micro-Prismatic Diffuser Dali







Metal cover. Surface / Suspension Down. 35 mm 08.9050.06 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40 500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00





Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS