











In-Finity 35 Surface Emergency 3000K General Lighting

N35SEM3G30B - White

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications Number of heads Lamp category Power (W) CCT (K) CRI	1 LED 28W 3000K 80	Net lumen (lm) Mountings Environment	1643 Surface Indoor dry location
Optical Lighting type LED type Light distribution Optical type Beam angle (°)	Direct Top LED Symmetric Diffused light 110	Beam angle C90-270 (°)	110
Electrical Voltage (V) Dimmable Driver Driver type Emergency	220.00 No Integrated Non Dimmable With	Insulation class	I
Physical Color Orientation Weight (kg) Length (mm)	White Fixed 3.19 1405		

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Surface Emergency 3000K General Lighting



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS