





## N35SFC3G02BDA - Anodized Grey

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.




Number of heads Lamp category LED Power (W) 22 5W CCT (K) 3000K CRI 80

Net lumen (lm) Mountinas Surface

Environment Indoor dry location

#### Optical


Lighting type Direct LED type Light distribution Top LED Symmetric Optical type Diffused light Beam angle (°) 110 Beam angle C90-270 (°) 110



 $E(I_X)$ D(m) h(m) 1 483 2.63 2 121 5.26 3 54 7.90 4 30 10.53 5 19 13.16

Beam Angle: 107°

Luminous flux luminaire 1315 lm















#### Electrical

Frequency (Hz) 50/60 Voltage (V) 220.00 Dimmable Yes Driver Integrated Driver type Dimmable DALI 1

Without **Emergency** Insulation class

#### **Physical**

Color Anodized Grey Orientation Fixed Weight (kg) 3.16 Length (mm) 568

### Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 35 Surface Flat Corner 3000K General Lighting Dali







500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00


Metal cover. Surface / Suspension Down. 35 mm 08.9050.06

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



(Colour White)

08.9050.40





Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS