





■ N35SFC3U14BDA - Black

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.


Main specifications


Number of heads	1
Lamp category	LED
Power (W)	22.5W
CCT (K)	3000K
CRI	80

Net lumen (lm) 1022 Mountings Surface

Environment Indoor dry location









Luminous flux luminaire 1022 lm

Beam Angle:		75°
h(m)	E(l x)	D(m
1	662	1.25
2	166	2.50
3	74	3.76
4	41	5.01
5	26	6.26



















Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI
	1

Emergency Insulation class Without

Physical

Black
Fixed
3.16
568

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Surface Flat Corner 3000K Micro-Prismatic Diffuser Dali







500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06