





LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.






Number of heads Net lumen (lm) 1022 Lamp category LED Mountings Surface Power (W) 22.5W Environment Indoor dry location CCT (K) 3000K CRI 80




## Optical

Lighting type Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 76 Beam angle C90-270 (°) 64



Luminous flux luminaire 1022 lm

Beam Angle:		75°
h(m)	E(lx)	D(m)
1	662	1.25
2	166	2.50
3	74	3.76
4	41	5.01
5	26	6 26



#### Electrical

Frequency (Hz) 50/60 220.00 Voltage (V) Dimmable Yes Driver Integrated Driver type Dimmable DALI

Without **Emergency** Insulation class















## Physical

Color White Orientation Fixed Weight (kg) 3.16 Length (mm) 568

#### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 35 Surface Flat Corner 3000K Micro-Prismatic Diffuser Dali



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06 500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS