

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Main specifications


Number of heads	1
Lamp category	LED
Power (W)	22.5W
CCT (K)	4000K
CRI	80

Net lumen (lm) Mountings Surface

Environment Indoor dry location



Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	76
Beam angle C90-270 (°)	64



h(m) E(lx)D(m) 717 1.25 2 179 2.50 3 80 3.76 5.01 4 45 5 29 6.26

Beam Angle:

75°

Luminous flux luminaire 1107 lm

Electrical

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Driver	Integrated
Driver type	Non Dimmahla

Emergency Insulation class

Without















Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	3.16
Length (mm)	568

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Surface Flat Corner 4000K Micro-Prismatic Diffuser







500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00

Metal cover. Surface / Suspension Down. 35 mm 08.9050.06

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS