





LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.



Number of heads	1
Lamp category	LED
Power (W)	22.5W
CCT (K)	4000K
CRI	80

Net lumen (lm) 1107 Mountings Surface

Environment Indoor dry location

Optical


Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	76
Beam angle C90-270 (°)	64

50/60

220.00

Non Dimmable

No Integrated



h(m) E(lx)D(m) 717 1.25 2 2.50 179 3 80 3.76 5.01 4 45 5 29 6.26

Beam Angle:

75°


Luminous flux luminaire 1107 lm

Emergency

Insulation class

Without







Physical

Driver type

Electrical
Frequency (Hz)

Voltage (V)

Dimmable

Driver

Color	ыаск
Orientation	Fixed
Weight (kg)	3.16
Length (mm)	568

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Surface Flat Corner 4000K Micro-Prismatic Diffuser







500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06