





N35D083G30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Number of heads	1
Lamp category	LED
Power (W)	16.5W
CCT (K)	3000K
CRI	80

Net lumen (lm) Mountings Environment


Suspension Indoor dry location



[]]8



Lighting type Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 110 Beam angle C90-270 (°) 110



2.63 363 2 91 5.26 7.90 3 40 4 23 10.53 15 13.16

Beam Angle: 107°

E(lx)

D(m)

h(m)

Luminous flux luminaire 986 lm

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		



Physical

Vhit∈
ixed
.92
345

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Down 3000K General Lighting Dali



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00



Power supply rose. Dali 08.0031.00.DA



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Suspension kit 08.0030