



In-Finity 35 Suspension Down 3000K General Lighting Dali

■ N35D303G02BDA - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.


Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 3616 |
| Lamp category | LED | Mountings | Suspension |
| Power (W) | 63.5W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 80 | | |



Optical

| | |
|-------------------------------|----------------|
| Lighting type | Direct |
| LED type | Top LED |
| Light distribution | Symmetric |
| Optical type | Diffused light |
| Beam angle (°) | 110 |
| Beam angle C90-270 (°) | 110 |



Beam Angle: 107°

| | | |
|------|-------|------|
| h(m) | E(lx) | D(m) |
|------|-------|------|

| | | |
|---|------|------|
| 1 | 1329 | 2.63 |
|---|------|------|


| | | |
|---|-----|------|
| 2 | 332 | 5.26 |
|---|-----|------|

| | | |
|---|-----|------|
| 3 | 148 | 7.90 |
|---|-----|------|

| | | |
|---|----|-------|
| 4 | 83 | 10.53 |
|---|----|-------|

| | | |
|---|----|-------|
| 5 | 53 | 13.16 |
|---|----|-------|

Luminous flux luminaire
3616 lm



85
38
35
31

Electrical


| | | | |
|-----------------------|---------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | |
|--------------------|---------------|
| Color | Anodized Grey |
| Orientation | Fixed |
| Weight (kg) | 7.03 |
| Length (mm) | 3095 |

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 35 Suspension Down 3000K General Lighting Dali



5



5

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey)
08.9050.02

Suspension kit
08.0030

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black)
08.9050.NS



5



5



Metal cover. Surface / Suspension Down. 35 mm
08.9050.06

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White)
08.9050.40

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0109.00



Power supply rose. Dali
08.0031.00.DA