





N35D113G02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Number of heads Lamp category LED Power (W) 22.5W 3000K CCT (K) CRI 80

Net lumen (lm) Mountings Environment

Suspension Indoor dry location










Optical

Lighting type Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 110 Beam angle C90-270 (°) 110



Luminous flux luminaire 1315 lm

Beam Angle:		107°
h(m)	E(lx)	D(m)
1	483	2.63
2	121	5.26
3	54	7.90
4	30	10.53
5	19	13 16

Electrical

Frequency (Hz) 50/60 **Emergency** Without Voltage (V) 220.00 Insulation class Dimmable No Driver Integrated

Non Dimmable

Physical

Driver type

Color Anodized Grey Orientation Fixed Weight (kg) 2.56 1125 Length (mm)

Note

 $Opal\,Diffuser:\,Diffuse,\,glare\,free\,and\,uniform\,lighting\,throughout\,the\,room.\,/\,Emergency:\,Emergency\,Module\,And Control of Control$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Down 3000K General Lighting



Power supply rose 08.0031.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Suspension kit 08.0030



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06