





■ N35D143U14B - Black

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Number of heads	1
Lamp category	LED
Power (W)	28W
CCT (K)	3000K
CRI	80

Net lumen (lm) Mountings Environment

Suspension Indoor dry location






Optical Lighting type LED type

Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)

Direct Top LED Symmetric Diffused light 76 64



Luminous flux luminaire 1278 lm

Without

Beam Angle:		/5°
h(m)	E(lx)	D(m)
1	828	1.25
2	207	2.50
3	92	3.76
4	52	5.01
5	33	6 26

-	L	_

85

ÆV102	\F7	L IP
400	V	20
		_













Electrical

Frequency (Hz)	50/60	Emergency
Voltage (V)	220.00	Insulation class
Dimmable	No	
Driver	Integrated	

Non Dimmable

Physical

Driver type

Black
Fixed
3.19
1405

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Down 3000K Micro-Prismatic Diffuser



Power supply rose 08.0031.00

(Colour Black)

08.9050.NS



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Suspension kit 08.0030



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



Metal cover. Surface / Suspension

