



In-Finity 35 Suspension Down 4000K General Lighting Dali

N35D084G02BDA - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

1
LED
16.5W
4000K
80

Net lumen (lm) Mountings Environment

1068 Suspension Indoor dry location






-	L	
	82	





Optical Li

Direct
Top LED
Symmetric
Diffused light
110
110



Luminous flux luminaire 1068 lm

Beam Angle:		107°
h(m)	E(l x)	D(m)
1	393	2.63
2	98	5.26
3	44	7.90
4	25	10.53
5	16	13 16

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	1
Dimmable	Yes		
Driver	Integrated		

Dimmable DALI

Physical

Driver type

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	1.92
Length (mm)	845

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Down 4000K General Lighting Dali







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00

Power supply rose. Dali 08.0031.00.DA



Metal End Cap. Recessed No Trim /

Surface / Suspension Down. 35 mm

(Colour Anodized Grey)

08.9050.02





Suspension kit 08.0030



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal cover. Surface / Suspension Down. 35 mm

08.9050.06