





K 03	V	І Р 20	EAC	CE	RETILAP
GWT 850°					

In-Finity 35 Suspension Down 4000K General Lighting Dali N35D144G30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications Number of heads Lamp category Power (W) CCT (K) CRI	1 LED 28W 4000K 80	Net lumen (lm) Mountings Environment	1779 Suspension Indoor dry location		
Optical					
Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)	Direct Top LED Symmetric Diffused light 110 110	90° 60° 30° 654 cd Luminous flux 1779 lm	N	Beam Angle: 107° h(m) E(lx) D(m) 1 654 2.63 2 164 5.26 3 73 7.90 4 41 10.53 5 26 13.16	
Electrical					
Frequency (Hz) Voltage (V) Dimmable Driver Driver type	50/60 220.00 Yes Integrated Dimmable DALI 1	Emergency Insulation class	Without I		
Physical					
Color Orientation Weight (kg) Length (mm)	White Fixed 3.19 1405				

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Down 4000K General Lighting Dali



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02 Suspension kit 08.0030

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06

5



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00



Power supply rose. Dali 08.0031.00.DA