



L []]120 355 338

<b>K</b> 03	V	<b>I</b> P 20	EAC	CE	RETILAP
GWT 850°		<u> </u>			

## In-Finity 35 Suspension Down 4000K General Lighting Dali N35D194G02BDA - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications Number of heads Lamp category Power (W) CCT (K) CRI	1 LED 41W 4000K 80	Net lumen (lm) Mountings Environment	2491 Suspension Indoor dry location			
Optical						
Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)	Direct Top LED Symmetric Diffused light 110 110	90° 60° 30° 916 cd Luminous flux I 2491 lm		1 9 2 2 3 1 4	216 229 02 57	107° D(m) 2.63 5.26 7.90 10.53 13.16
Electrical						
Frequency (Hz) Voltage (V) Dimmable Driver Driver type	50/60 220.00 Yes Integrated Dimmable DALI 1	Emergency Insulation class	Without I			
Physical						
Color Orientation Weight (kg) Length (mm)	Anodized Grey Fixed 4.48 1970					

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

## In-Finity 35 Suspension Down 4000K General Lighting Dali



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40 500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00 Power supply rose. Dali 08.0031.00.DA



5 Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Suspension kit 08.0030



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06