



# In-Finity 35 Suspension Down 4000K General Lighting Dali

#### N35D254G30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

#### Main specifications

Number of heads	1
Lamp category	LED
Power (W)	50W
CCT (K)	4000K
CRI	80


Net lumen (lm) Mountings Environment

3203 Suspension Indoor dry location





Lighting type Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 110 Beam angle C90-270 (°) 110



Luminous flux luminaire 3203 lm

Beam Angle:		107°
h(m)	E(lx)	D(m)
1	1178	2.63
2	294	5.26
3	131	7.90
4	74	10.53
5	47	13 16

[]]8

lectrical	

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		



### **Physical**

Color	White
Orientation	Fixed
Weight (kg)	5.75
Length (mm)	2530

## Note

 $Opal\ Diffuser: Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 35 Suspension Down 4000K General Lighting Dali



Power supply rose. Dali 08.0031.00.DA



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Suspension kit 08.0030



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room

