



# In-Finity 35 Suspension Down 4000K General Lighting

## N35D194G02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

### Main specifications

Number of heads	1
Lamp category	LED
Power (W)	41W
CCT (K)	4000K
CRI	80

Net lumen (lm) Mountings Environment

2491 Suspension Indoor dry location






Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)

Optical Lighting type

LED type

Direct Top LED Symmetric Diffused light 110 110



Luminous flux luminaire 2491 lm

Without

**Emergency** 

Insulation class

Beam	Angle:	107°
h(m)	E(lx)	D(m)
1	916	2.63
2	229	5.26
3	102	7.90
4	57	10.53
5	37	13 16



[]]



#### Electrical

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Driver	Integrated

D Driver type Non Dimmable

## **Physical**

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	4.48
Length (mm)	1970

## Note

 $Opal\,Diffuser:\,Diffuse,\,glare\,free\,and\,uniform\,lighting\,throughout\,the\,room.\,/\,Emergency:\,Emergency\,Module\,And Control of Control$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

## In-Finity 35 Suspension Down 4000K General Lighting



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Suspension kit 08.0030



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00



Power supply rose 08.0031.00