



In-Finity 35 Suspension Down 4000K General Lighting


■ N35D254G14B - Black

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications


Number of heads	1
Lamp category	LED
Power (W)	50W
CCT (K)	4000K
CRI	80

Net lumen (lm) Mountings Environment 3203 Suspension Indoor dry location






Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°) Direct Top LED Symmetric Diffused light 110 110



Luminous flux luminaire 3203 lm

Bea	m Angle:	107°
h(m)) E(lx)	D(m
1	1178	2.63
2	294	5.26
3	131	7.90
4	74	10.53
5	17	12 14



158 35 38

/#1/on	\F7	IP	COL	((RETILAF
# # Jan	🔍	20	CUL	7	KETIDAI
GWT		$\overline{\Box}$			

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	I
Dimmable	No		
Driver	Integrated		

Non Dimmable

Physical

Driver type

Color	Black
Orientation	Fixed
Weight (kg)	5.75
Length (mm)	2530

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Down 4000K General Lighting







Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00

Power supply rose 08.0031.00



Metal End Cap. Recessed No Trim /

Surface / Suspension Down. 35 mm

(Colour Anodized Grey)

08.9050.02






Suspension kit 08.0030



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS





Down. 35 mm 08.9050.06