



# In-Finity 35 Suspension Down 4000K Micro-Prismatic Diffuser

#### N35D114U30B - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

#### Main specifications

1
LED
22.5W
4000K
80

Net lumen (lm) Mountings Environment

Suspension Indoor dry location








83

<b>4</b> 03	\$ <b>I</b> P 20	EAL CE RETILAP
GWT		

Direct
Top LED
Symmetric
Diffused light
76
54



Luminous flux luminaire 1107 lm

Beam	75	
h(m)	E( <b>l</b> ×)	D(m
1	717	1.25
2	179	2.50
3	80	3.76
4	45	5.01
5	29	6.26

#### Electrical

Optical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	I
Dimmable	No		
Driver	Integrated		

Non Dimmable

### Physical

Driver type

White
Fixed
2.56
1125

#### Note

 $Micro-Prismatic \ Diffuser: Highly \ efficient \ multilayer \ diffuser \ that, thanks \ to \ its \ unique \ micro-prismatic \ texture,$ provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

## In-Finity 35 Suspension Down 4000K Micro-Prismatic Diffuser



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



Power supply rose 08.0031.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Suspension kit 08.0030



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal cover. Surface / Suspension

