



In-Finity 35 Suspension Down 4000K Micro-Prismatic Diffuser N35D194U02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications

Number of heads	1
Lamp category	LED
Power (W)	41W
CCT (K)	4000K
CRI	80

Net lumen (lm) Mountings Environment

1937 Suspension Indoor dry location






Lighting type LED type Light distribution Optical type

Optical

Beam angle (°) Beam angle C90-270 (°)

Direct Top LED Symmetric Diffused light 76 64



Luminous flux luminaire 1937 lm

Without

Emergency

Insulation class

Beam Angle:		75°
h(m)	E(lx)	D(m
1	1255	1.25
2	314	2.50
3	139	3.76
4	78	5.01
5	50	6 26

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Deiror	late are to d

Integrated Driver type Non Dimmable

EHE CE RETILAP

[]]





Physical

Electrical

Color	Anodized Grey	
Orientation	on Fixed	
Weight (kg)	4.48	
Length (mm)	1970	

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Down 4000K Micro-Prismatic Diffuser







Suspension kit 08.0030

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS

Metal cover. Surface / Suspension Down. 35 mm 08.9050.06







500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam 08.0112.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40

Power supply rose 08.0031.00



Metal End Cap. Recessed No Trim /

(Colour Anodized Grey) 08.9050.02		
00.7000.02		