









In-Finity 35 Suspension Down Emergency 3000K General Lighting Dali

N35DEM3G02BDA - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main specifications					
Number of heads Lamp category Power (W) CCT (K) CRI	1 LED 28W 3000K 80	Net lumen (lm) Mountings Environment	1643 Suspension Indoor dry location		
Optical					

O p 1.00.		
Lighting type	Direct	Beam angle C90-270 110
LED type	Top LED	(°)
Light distribution	Symmetric	

Optical type Diffused light

Beam angle (°) 110

Electrical			
Voltage (V)	220.00	Insulation class	1
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
	1		
Emergency	With		

Physical		
Color	Anodized Grey	
Orientation	Fixed	
Weight (kg)	3.19	
Length (mm)	1405	

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Down Emergency 3000K General Lighting Dali



Power supply rose. Dali 08.0031.00.DA



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Suspension kit 08.0030



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room

