









## In-Finity 35 Suspension Down Emergency 3000K General Lighting

### N35DEM3G02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

Main	specif	ications
------	--------	----------

Number of heads	1	Net lumen (lm)	1643
Lamp category	LED	Mountings	Suspension
Power (W)	28W	Environment	Indoor dry location
CCT (K)	3000K		

### Optical

CRI

Lighting type	Direct	Beam angle C90-270 110
LED type	Top LED	(°)
Light distribution	Symmetric	
Optical type	Diffused light	
Beam angle (°)	110	

80

#### **Electrical**

Voltage (V)	220.00	Insulation class	- 1
Dimmable	No		
Driver	Integrated		

Non Dimmable With

#### **Physical**

Driver type

**Emergency** 

•		
Color	Anodized Grey	
Orientation	Fixed	
Weight (kg)	3.19	
Length (mm)	1405	

#### Note

 $Opal\ Diffuser: Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

# In-Finity 35 Suspension Down Emergency 3000K General Lighting



Power supply rose 08.0031.00



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey) 08.9050.02



Suspension kit 08.0030



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black) 08.9050.NS



Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White) 08.9050.40



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00



Metal cover. Surface / Suspension Down. 35 mm 08.9050.06