

In-Finity 35 Suspension Down Flat Corner 3000K General Lighting

N35DFC3G02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.



Main specifications

Number of heads	1	**Net lumen (lm)**	1315
Lamp category	LED	**Mountings**	Suspension
Power (W)	22.5W	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



Luminous flux luminaire
1315 lm

Beam Angle: 107°

h(m)	E(lx)	D(m)
1	483	2.63
2	121	5.26
3	54	7.90
4	30	10.53
5	19	13.16

Electrical

Frequency (Hz)	50/60	**Emergency**	Without
Voltage (V)	220.00	**Insulation class**	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	3.16
Length (mm)	568

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-FInity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Down Flat Corner 3000K General Lighting

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0109.00

Power supply rose
08.0031.00

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Anodized Grey)
08.9050.02

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour White)
08.9050.40

Metal End Cap. Recessed No Trim / Surface / Suspension Down. 35 mm (Colour Black)
08.9050.NS

Metal cover. Surface / Suspension Down. 35 mm
08.9050.06

Suspension kit
08.0030