In-Finity 35 Suspension Up & Down 3000K General Lighting Dali

N35U163G02BDA - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.



Main specifications

Number of heads	1	**Net lumen (lm)**	3195
Lamp category	LED	**Mountings**	Suspension
Power (W)	57W	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



Luminous flux luminaire
3195 lm

Beam Angle DIR: 107°

h(m)	E(lx)	D(m)
1	725	2.63
2	181	5.26
3	81	7.90
4	45	10.53
5	29	13.16

Electrical

Frequency (Hz)	50/60	**Emergency**	Without
Voltage (V)	220.00	**Insulation class**	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI 1		

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	3.84
Length (mm)	1690

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-FInity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down 3000K General Lighting Dali

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0109.00

Power supply rose. Dali
08.0031.00.DA

Metal cover. Suspension Up & Down. 35 mm
08.9056.06

Metal cover. Suspension Up & Down. 35 mm (Colour Black)
08.9056.NS

Suspension kit
08.0030

Metal cover. Suspension Up & Down. 35 mm (Colour Anodized Grey)
08.9056.02

Metal cover. Suspension Up & Down. 35 mm (Colour White)
08.9056.40