



In-Finity 35 Suspension Up & Down 3000K General Lighting Dali

N35U303G02BDA - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


Main specifications

Number of heads	1	Net lumen (lm)	5858
Lamp category	LED	Mountings	Suspension
Power (W)	103W	Environment	Indoor dry location
CCT (K)	3000K		

Optical

Lighting type Indirect, Direct
LED type Top LED
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 110
Beam angle C90-270 (°) 110

80



h(m)	E(lx)	D(m)
1	1329	2.63
2	332	5.26
3	148	7.90
4	83	10.53
5	53	13.16

Beam Angle DIR: 107°

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable DALI		
• •			

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	7.03
Length (mm)	3095

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down 3000K General Lighting Dali



Metal cover. Suspension Up & Down. 35 mm (Colour Anodized Grey) 08.9056.02



Metal cover. Suspension Up & Down. 35 mm (Colour White) 08.9056.40



Power supply rose. Dali 08.0031.00.DA



Suspension kit 08.0030



Metal cover. Suspension Up & Down. 35 mm 08.9056.06



Metal cover. Suspension Up & Down. 35 mm (Colour Black) 08.9056.NS



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00