



# In-Finity 35 Suspension Up & Down 3000K General Lighting

N35U113G02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

#### Main specifications

1
LED
36.5W
3000K
80


Net lumen (lm) Mountings Environment

2130 Suspension Indoor dry location





Lighting type Indirect, Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 110 Beam angle C90-270 (°) 110



Luminous flux luminaire 2130 lm


Beam A	Angle DIR	8: 107
h(m)	E(lx)	D(m)
1	483	2.63
2	121	5.26
3	54	7.90
4	30	10.53
5	10	13 16

		35

Fr

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Driver	Integrated

**Emergency** Insulation class Without



## Driver type Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	2.56
Length (mm)	1125

Non Dimmable

#### Note

 $Opal\,Diffuser:\,Diffuse,\,glare\,free\,and\,uniform\,lighting\,throughout\,the\,room.\,/\,Emergency:\,Emergency\,Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

## In-Finity 35 Suspension Up & Down 3000K General Lighting





Metal cover. Suspension Up & Down. 35 mm (Colour Black) 08.9056.NS

Metal cover. Suspension Up & Down. 35 mm (Colour Anodized Grey) 08.9056.02

Metal cover. Suspension Up & Down. 35 mm (Colour White) 08.9056.40



Metal cover. Suspension Up & Down. 35 mm 08.9056.06



Power supply rose 08.0031.00



Suspension kit 08.0030



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0109.00