In-Finity 35 Suspension Up & Down 3000K General Lighting

N35U253G30B - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	**Net lumen (lm)**	4793
Lamp category	LED	**Mountings**	Suspension
Power (W)	82.5W	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	110
Beam angle C90-270 (°)	110



Luminous flux luminaire
4793 lm

Beam Angle DIR: 107°

h(m)	E(lx)	D(m)
1	1088	2.63
2	272	5.26
3	121	7.90
4	68	10.53
5	44	13.16



Electrical

Frequency (Hz)	50/60	**Emergency**	Without
Voltage (V)	220.00	**Insulation class**	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

Color	White
Orientation	Fixed
Weight (kg)	5.75
Length (mm)	2530

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-FInity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down 3000K General Lighting

Metal cover. Suspension Up & Down. 35 mm (Colour Anodized Grey)
08.9056.02

Metal cover. Suspension Up & Down. 35 mm (Colour White)
08.9056.40

Power supply rose
08.0031.00

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0109.00

Suspension kit
08.0030

Metal cover. Suspension Up & Down. 35 mm
08.9056.06

Metal cover. Suspension Up & Down. 35 mm (Colour Black)
08.9056.NS