In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser

N35U113U14B - Black

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.



Main specifications

Number of heads	1	**Net lumen (lm)**	1838
Lamp category	LED	**Mountings**	Suspension
Power (W)	36.5W	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	76
Beam angle C90-270 (°)	64



Luminous flux luminaire
1838 lm

Beam Angle DIR: 75°

h(m)	E(lx)	D(m)
1	662	1.25
2	166	2.50
3	74	3.76
4	41	5.01
5	26	6.26

Electrical

Frequency (Hz)	50/60	**Emergency**	Without
Voltage (V)	220.00	**Insulation class**	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		



Physical

Color	Black
Orientation	Fixed
Weight (kg)	2.56
Length (mm)	1125

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-FInity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser

Metal cover. Suspension Up & Down. 35 mm (Colour Anodized Grey)
08.9056.02

Metal cover. Suspension Up & Down. 35 mm (Colour White)
08.9056.40

Power supply rose
08.0031.00

500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam
08.0112.00

Metal cover. Suspension Up & Down. 35 mm
08.9056.06

Metal cover. Suspension Up & Down. 35 mm (Colour Black)
08.9056.NS

Suspension kit
08.0030